



Electrical Driven Single stage and 2 Stage Dry Vacuum Pumps

Producing a vacuum for modern industrial applications requires a method of air removal that is simple, dependable and economical to operate and maintain. All of these requirements are met by the Ingersoll Rand T30 air-cooled reciprocating single-stage and two-stage vacuum pumps.

Features

- These pumps achieve vacuum upto 737mm (29.0" Hg) for single stage and upto 754.4mm (29.7" Hg) for two stage configuration, at sea level.
- These dry type vacuum pumps are ideal for paper handling, food processing, vacuum forming, liquid transfer and many other applications.



Model Specifications

Model	Piston Displacement (cfm)	Vacuum (Hg) inch	Motor (hp)
V235	21.60	29.00	1.5
V235T	10.80	29.60	1.5
V244	34.60	29.00	2.0
V244T	17.30	29.65	2.0
V255	60.00	29.00	5.0
V255T	30.00	29.70	5.0
7V	110.00	29.00	7.5
7VT	55.00	29.65	7.5
15V	149.60	29.20	10.0

Parts & Accessories



F-Series Filters



Electronic Drain Valves



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRco.com.